


# Meyer Burger White

## Heterojunction Module



### Maximum performance

Up to 20 percent more energy yield – even in low-light conditions, such as in the morning and evening hours or with cloudy skies




### Maximum quality

Production of solar cells and modules according to the highest standards and exclusively in Germany




### Maximum durability

Guaranteed yields for decades



### Maximum stability

Patented SmartWire technology makes the modules extremely rugged and efficient




### Maximum elegance

Understated and superb design – invented in Switzerland

### Meyer Burger (Industries) GmbH


Carl-Schiffner-Str. 17  
09599 Freiberg  
Germany

[www.meyerburger.com](http://www.meyerburger.com)



## MECHANICAL SPECIFICATION

Dimensions [mm]	1,767 x 1,041 x 35
Weight [kg]	19.7
Front cover	Solar glass, 3.2 mm, with anti-reflective surface
Back cover	High-barrier construction, white
Frame	Anodized aluminum (black)
Solar cell type	120 half-cut, mono n-Si, HJT
Junction boxes	3 diodes, IP68 rated, in accordance with IEC 62790
Cable	PV cable 4 mm <sup>2</sup> , 1.2 m length, in accordance with EN 50618
Connectors	MC4, in accordance with IEC 62852, IP68 rated only when connected



## ELECTRICAL SPECIFICATION<sup>1</sup>


Power class in STC <sup>2</sup> [W <sub>p</sub> ]			380		385		390		395		400	
Minimum Performance (Power Tolerance -0 W/+5 W) [W <sub>p</sub> ]	STC		NMOT <sup>3</sup>		STC		NMOT		STC		NMOT	
	Power at MPP	P <sub>mpp</sub>	[W]	380	291	385	294	390	299	395	301	400
Short Circuit Current	I <sub>sc</sub>	[A]	10.8	8.7	10.9	8.8	10.9	8.8	11.0	8.9	11.1	9.0
Open Circuit Voltage	V <sub>oc</sub>	[V]	44.4	41.8	44.5	41.9	44.5	41.9	44.6	42.0	44.7	42.1
Current at MPP	I <sub>mp</sub>	[A]	10.3	8.3	10.3	8.3	10.4	8.4	10.4	8.4	10.5	8.5
Voltage at MPP	V <sub>mp</sub>	[V]	37.2	35.1	37.6	35.4	37.8	35.6	38.0	35.8	38.2	36.0
Efficiency	η	[%]	20.7		20.9		21.2		21.5		21.7	

### Temperature Coefficients

Temperature Coefficient of I <sub>sc</sub>	α	[%/°C]	+0.033
Temperature Coefficient of V <sub>oc</sub>	β	[%/°C]	-0.234
Temperature Coefficient of P <sub>MPP</sub>	γ	[%/°C]	-0.259
Nominal Module Operating Temperature	NMOT <sup>3</sup>	[°C]	44±2

The temperature coefficients stated are linear values

### Performance at different irradiance



## PROPERTIES FOR SYSTEM DESIGN

Maximum System Voltage	[V]	1,000
Maximum Series Fuse Rating	[A]	15
Max. Test Load +/- (incl. Safety Factor of 1.5)	[Pa]	6,000/4,000
Fire class according to EN 13501-1		B2
Operation Temperature	°C	-40 to +85

## MEYER BURGER WARRANTY

Product Warranty [y]	25
Power Warranty [y]	25
Power after 1 year	≥98% of nominal power
Annual Degradation [%/y]	0.25
Power after 25 years	≥92% of nominal power

Warranty conditions apply

## CERTIFICATES

### Certifications

IEC 61215:2016, IEC 61730:2016

### Certifications (to come)

UL61730-1, UL 61730-2, PID (IEC 62804), Salt Mist (IEC 61701), Ammonia Resistance (IEC 62716), Dynamical Mechanical Load (IEC, 62782:2016), Dust & Sand (IEC 60068)

Notice: All data and specifications are preliminary and subject to change without notice.

Made in Germany.  
Designed in Switzerland.



WEEE-Reg.-Nr. DE 18170271

<sup>1</sup> Measurement according to IEC 60904-3, measurement tolerance: ±3%, monofacial measurement with rear side covered  
<sup>2</sup> STC: Irradiance 1000 W/m<sup>2</sup>, 25 °C, AM1.5 Spectrum  
<sup>3</sup> NMOT: Nominal Module Operating Temperature, with irradiance 800 W/m<sup>2</sup>, AM1.5 Spectrum, 20 °C, wind speed 1 m/s